


## Model TPD3135A8

### Features

Excellent phase& amplitude balance  
 Low Insertion Loss& VSWR  
 High Isolation


Technical Data Sheet			
Frequency Range	3.1~3.5GHz	Finish	Painted Blue_ RAL #5007
Insertion Loss	≤0.6dB (Above 9.03dB Split)	Connector Body	Passivated Stainless Steel
VSWR	Input ≤1.30:1 Output ≤1.20:1	Housing	Aluminum, 6061 T6 Clear Chem Conversion Film
Isolation	≥23dB	Connector Pin	Beryllium Copper, Gold Plate
Amplitude Balance	≤±0.2dB	Solder	Lead Free, RoHS Compliant
Phase Balance	≤±2°	Operating Temperature	-55~+85°C
<sup>1</sup> Power Handling	Forward ≤30Watt; Reversed ≤1Watt	Operating Humidity	Up to 95%, Non- Condensing
Impedance	50Ω	Weight	160g
Port Connectors	SMA-Female		

<sup>1</sup>Power Handling guaranteed when load's VSWR within 1.50:1.




## Typical Performance

### 1. Insertion Loss, Amplitude &Phase Balance, VSWR



Date: 4.FEB.16 09:29:06

### 2. Isolation



Date: 4.FEB.16 10:28:25

