


## Model THC2060B1

### Features

Excellent phase & amplitude balance  
Low Insertion Loss & VSWR  
High Isolation

Technical Data Sheet			
Frequency Range	2~6GHz	Finish	Painted Blue_ RAL #5007
Nominal Split	3.01dB	Connector Body	Passivated Stainless Steel
Insertion Loss	≤1.4dB	Housing	Aluminum, 6061 T6
Isolation	≥18dB		Clear Chem Conversion Film
Amplitude Balance	≤±0.8dB	Connector Pin	Beryllium Copper, Gold Plate
Phase Balance	≤±12°	Solder	Lead Free, RoHS Compliant
VSWR	≤1.50:1	Operating Temperature	-55~+85°C
<sup>1</sup> Power Handling	Average ≤50Watt Peak ≤1KW	Operating Humidity	Up to 95%, Non-Condensing
Impedance	50Ω	Weight	110g
Port Connectors	SMA-Female		

<sup>1</sup>Power Handling guaranteed when load's VSWR within 1.50:1.




## Typical Performance


### 1. Insertion Loss, Amplitude & Phase Balance, VSWR<sub>in</sub> 0°




Trc1 **S11** SWR 100 mU/ Ref 1 U Cal  
Mem5[Trc1] **S21** SWR 100 mU/ Ref 1 U Invis




Trc2 **S21** Phase unwrap 12° / Ref 0°  
Mem6[Trc2] **S21** Phase unwrap 12° / Ref 0°



Trc3 **S21** dB Mag 0.8 dB / Ref -3 dB C  
Mem7[Trc3] **S21** dB Mag 0.8 dB / Ref -3 dB



Trc4 **S22** SWR 100 mU/ Ref 1 U Cal 4




12/18/2019, 11:22 PM




## Typical Performance

### 2. Insertion Loss, Amplitude & Phase Balance, VSWR \_ 180°



12/18/2019, 11:23 PM

### 3. Isolation



12/18/2019, 11:30 PM

