


## Model TDC2040A10

### Features

Low VSWR  
High Directivity  
Broadband & Miniature Size

Technical Data Sheet			
Frequency Range	2~4GHz	Finish	Painted Blue_ RAL #5007
Insertion Loss	≤0.3dB (Excl. Coupling Loss 0.46dB)	Connector Body	Passivated Stainless Steel
Coupling Factor	≤10±0.7dB	Housing	Aluminum, 6061 T6 Clear Chem Conversion Film
Coupling Sensitivity	≤±0.7dB	Connector Pin	Beryllium Copper, Gold Plate
Directivity	≥22dB	Solder	Lead Free, RoHS Compliant
VSWR	Primary ≤1.15:1 Secondary ≤1.15:1	Operating Temperature	-55~+85°C
<sup>1</sup> Power Handling	Incident ≤50Watt; Reflected ≤2Watt	Operating Humidity	Up to 95%, Non- Condensing
Impedance	50Ω	Weight	30g
Port Connectors	SMA-Female		

<sup>1</sup>Power Handling guaranteed when load's VSWR within 1.50:1.




## Typical Performance


### 1. Coupling Factor & Sensitivity, Isolation, VSWR




Trc1 Mem5[Trc1] S11 SWR 100 mU/ Ref1 U Cal Invis




Trc2 Mem6[Trc2] S21 dB Mag 5 dB / Ref-32 dB In



Trc3 Mem7[Trc3] S21 dB Mag 0.7 dB / Ref-9.93 dB



Trc4 Mem8[Trc4] S22 SWR 100 mU/ Ref1 U Cal Invis




10/26/2020, 4:29 PM

### 2. Insertion Loss



Trc3 Mem7[Trc3] S21 dB Mag 0.1 dB / Ref-0.76 dB Cal Invisible 3 (Max)



10/26/2020, 4:30 PM

