


## Model THC60200A

### Features

Excellent phase & amplitude balance  
 Low Insertion Loss & VSWR  
 High Isolation


Technical Data Sheet			
Frequency Range	6~20GHz	Finish	Painted Blue_ RAL #5007
Nominal Split	3.01dB	Connector Body	Passivated Stainless Steel
Insertion Loss	≤1.5dB	Housing	Aluminum, 6061 T6
Isolation	≥15dB		Clear Chem Conversion Film
Amplitude Balance	≤±0.7dB	Connector Pin	Beryllium Copper, Gold Plate
Phase Balance	≤±5°	Solder	Lead Free, RoHS Compliant
VSWR	≤1.40:1	Operating Temperature	-55~+85°C
<sup>1</sup> Power Handling	Average ≤20Watt Peak ≤1KW	Operating Humidity	Up to 95%, Non-Condensing
Impedance	50Ω	Weight	30g
Port Connectors	SMA-Female		

<sup>1</sup>Power Handling guaranteed when load's VSWR within 1.50:1.



## Typical Performance

### 1. Insertion Loss, Amplitude & Phase Balance, VSWR




9/2/2024, 9:09 AM




## Typical Performance

### 2. Insertion Loss, Amplitude & Phase Balance, VSWR



9/2/2024, 9:10 AM

### 3. Isolation



9/2/2024, 9:08 AM

